2021-02-24 5G-xHaul Meeting notes

24 Feb 2021 | 6am PST | 6am EST | 10:00 UTC | 11:00 CET | 12:00 EET | 15:30 IST | 18:00 CST | 19:00 JST |

Web Conference:

https://thorsten-heinze-telefonica-de.webex.com/join/andreas.lattoch.external

Attendees

- Alex Stancu
- Andrea Delmonte
- @Andreas Lattoch
- Alok Surve
- Daniela Spreafico **
- Daniel Perez Calvo
- Danilo Pala
- Eduardo Yusta **
- Hubing
- Hsudarsa Jorge Lopez
- Istvan Vencz
- Jasper Yang
- Leo
- Ma Yong
- Michael Binder
- Nader Zein
- Paul Parva
- Pawel Krecicki
- Petr Jurcik
- Prathiba
- Roberto Servadio **
- Shuzhan
- Thomas Seitz
- Thomas Schulze
- Tian Zhu
- Thorsten Heinze
- Yossi
- Zhang Dong
- Martin Skorupski **

Info to:

Tracy Van Brakle

Goals

• going forward

(please feel free to correct and update your names 3 Thank you very

Discussion items

Time	Item	Who	Notes
00:00	chair topic		no update
00:00	Admin		Next meetings
			2020-03-03: Martin Skorupski
			2020-03-10: Martin Skorupski
			2020-03-17: Martin Skorupski
			2020-03-24: Martin Skorupski

00:00	Firmware RPCs	Thorsten Heinze @Eduar do Yusta	 abort of download Constrain: only one download per ControlContruct (device): as input: https://www.o-ran.org/specifications - please see O-RAN Management Plane Specification - YANG Models 4.0 - July 2020 O-RAN.WG4.MP-YANGS-v04.00 \(\text{O-RAN.WG4.MP-YANGS-v04.00_zip\Common Models\Operations\o-ran-file-management.yang}\) as input: https://github.com/OpenROADM/OpenROADM_MSA_Public/blob/master/model/Device/org-openroadm-file-transfer.yang no destination needed - it ends in the currently not active bank. force option abort of download activate firmware activating stand-by is same as deactivating active
			Notification required alarm vs attribute-value-chance (trend: status attributes with AVC) RPC return value vs notification (trend: notification) Status values are needed in any case, for cases where notifications are lost Thorsten to send a proposal for further discussions GlobalClass vs LocalClass Agenda for tomorrow MediatorComponents
	End of the		
	Discussions to be continued:		
00:05	FC VLAN Creation	Thorsten Heinze	RPC for FD:VLAN-FC creation yang RPC- FC creation input FD:uuid to address the FD vlanid the "real" interesting parameter vlanid the "real" interesting parameter voltput FC:uuid now the FC:uuid is known to all application. The FC has no FCports at this point in time. yang RCP - target: creation for FCPorts input FC:uuid PC:uuid port role?!?! associations to LTP(VLAN) Continue the discussion on 2020-10-21 YANG provided by email and openBackhaul (link) new: RPC at the end - please check!!! new: "port-and-protocol-based-vlan-is-avail" renamed: "llc-address" to "llc-address-list" 2020-02-03 updates made on the error messages

00:00 Firmware @Eduar Eduardo explained his proposal about how to describe firmware (https://groups.google.com/a/opennetworking.org/g /wireless-transport/c/3BJHnPa5PRU) and addressed a couple of questions to the vendors. do Yusta Continuing the discussion about firmware. NEC provided input and it was consolidated in the proposal. How to activate a software package: leaf or RPC? Discussions still needed, RPC is preferred, need to see how to model and how to integrate in our processes (Papyrus, UML2YANG etc.) Alex Stancu to provide example from O-RAN FH model about how it is done in o-ran-software-management; then we can assess how we can adapt it to our needs. SIAE is checking if RPC is feasible; Nokia will also do some checking. maybe RPCs will be useful in other situations as well, we need to see Do we need also a Download RPC? Probably. But this could be considered outside of the package model, does not really influence the inventory part. Is ImageName (string) and ImageVersion (string) combination enough for uniquely identify a software image? ImageSize proposed to be eliminated. No objections. ImageClass - need tot see what happens if the case vendors do not support it; same for ImageIdentifier ImageComparison proposed to be eliminated. No objections. Need further discussions. 2020-01-13: Package Activation: attribute vs RPC ■ RPC seams to be the way forward ■ impact on UML/UML2YANG/YANG similar discussion for FC(VLAN) creation via RPC ■ UML/YANG modeling guideline uses term "operations" (not PRC) investigation ongoing Package Activation will gain by the VLAN-FC creation Parameter (status report and further discussion) Package Image regarding "imageIdentifier" - proposal to be discarded - however feedback from vendor will drive final decision Package and Image class should inherit from GlobalClass - same as for Profile 2020-01-20 **UML** for Firmware Firmware model as on conditional package for Controlconstruct 2020-02-03 https://groups.google.com/a/opennetworking.org/g/wireless-transport/c/I4-6I81JZoI

Action items